OVNATANOV, S.T., TAMRAZYAN, G.P.

Recovery factors for horizons y and 6a in the Surakhany oil field.
Neft. khoz. 38 no.1:50-56 Ja '60.   (MIRA 13:7)
(Oil fields—Production methods)

OVSNATANOV, S.T., TAMRAZYAN, G.P.

Changes in the quality of petroleums in certain fields of the
Apsheron Peninsula. Azerb. neft. khoz. 39 no.5:8-10 My '60.
(MIRA 13:10)

(Apsheron Peninsula—Petroleum—Analysis)

OVNATANOV, S.T.; TAMRAZYAN, G.P.

Thermal conditions and their significance for the study of
abyssal tectonics in the southern part of the Apsheron
Peninsula and the adjacent littoral zone. Dokl. AN SSSR 135
no.2:403-406 N '60.   (MIRA 13:11)

1. Trest Ordzhonikidzeneft' Ob"yedineniya Azneft' i Institut
geologii AN AzeSSR. Predstavleno akademikom A.A.Trofimukom.
        (Apsheron Peninsula--Geology, Structural)
              (Earth temperature)

TAMRAZYAN, G.P.

Characteristics of the distribution of gas resources in
the Apsheron region. Uch. zap. AGU. Ser. geol. geog. nauk
no.1:41-45 '61.   (MIRA 16:8)

OVHATAMOV, S.T.; GORIN, V.A.; TAMRAZYAN, G.P.

Geology of the Kirmaku Ridge.   Izv.AN Azerb.SSR, Ser.geol.-geog.
nauk i nefti no.5:41-53 '61.   (MIRA 15:1)
           (Apsheron Peninsula--Petroleum geology)
           (Apsheron Peninsula--Gas, Natural--Geology)

TAMRAZYAN, G.P.

Time of onset of tsunamis. Uch.zap.AGU. Geol.-geog.ser. no.6:
89-96 '61.   (MIRA 16:1)
(Caspian Sea--Tidal waves)

TAMRAZYAN, G.P.

Study of the tectonic characteristics of oil and gas bearing regions of eastern Azerbaijan taking into account the numerical folding indices. Trudy Inst.geol. AN Azerb. SSR 21:111-146 '61.

(MIRA 14:11)

(Azerbaijan—Folds(Geology))
(Azerbaijan—Petroleum geology)
(Azerbaijan—Gas, Natural)

S/049/62/000/001/003/003
D218/D304

AUTHOR: Tamrazyan, G.P.

TITLE: On the periodicity in seismic activity during the last one-
               and-half to two thousand years (the example of Armenia)

PERIODICAL: Akademiya nauk SSSR. Izvestiya. Seriya geofizicheskaya,
               no. 1, 1962, 76-85

TEXT: It is pointed out that Armenia is the only territorial region in
the USSR, for which there are factual earthquake data both for the second
and the first millennium of the present era. The author has made use of
all the existing data. A figure shows the distribution of the most
powerful earthquakes on the territory of historical Armenia and some of
the adjacent countries between 700 and 1950 AD. The figure shows that
there are half-periods of enhanced seismic activity which are of 45-70
year duration and are separated by half-periods of reduced activity ex-
tending over 40-75 years. This would indicate that there should be an
enhancement in the mean seismic activity in 2000-2060 or somewhat later.

Card 1/2

On the periodicity ...

S/049/62/000/001/003/003
D218/D304

The second part of this paper is concerned with the periodicity in the seismic activity as a special case of a periodicity rhythm in the release of internal energy. A general review is made of the principal periods of motion, development and release of the energy of the Earth's crust. It is shown that there exists a migration of high seismic activity zones. The presence of this migration is suggested both for the Soviet territory and for the American Continent (Central and South America). Long period trends in the direction of this migration are suggested both for the Soviet Union and the American Continent. The relation between catastrophic earthquakes and the deformation of the Earth as a whole is emphasized and it is suggested that this should be studied further. There are 4 figures, 1 table and 16 references: 15 Soviet-bloc and 1 non-Soviet-bloc. The reference to the Englishlanguage publication reads as follows: E.N. Nishimura, Dis. Prev. Inst. Kyoto Univ. Bull., n. 6, 1953.

SUBMITTED: June 3, 1960

Card 2/2

TAMRAZYAN, G. P.

A role of cosmic factors in the manifestation of mud volcanism.
Uch. zap. AGU. Geol.-geog. ser. no.1:87-94 '62.
                                                        (MIRA 16:1)

(Azerbaijan—Mud volcanoes)
(Cosmic physics)

GRIGOR'YANTS, B.V.; TAMRAZYAN, G.P.

Subsurface extension of the Kechaldag fqld within the boundaries
of the Baku syncline and its oil and gas potentials. Izv.AN
Azerh.SSR.Ser.geol.-geog.nauk i nefti no.3:23-31 '62.
(MIRA 15:12)
(Apsheron peninsula—Petroleum geology)
(Apsheron peninsula—Gas,Natural—Geology)

TAMRAZYAN, G. P.

On the existence of terrestrial pulsations related to the
solar cycle. Dokl. AN SSSR 147 no.6:1361-1364 D '62.
(MIRA 16:1)

1. Predstavleno akademikom D. V. Nalivkinym.

(Geology, Structural)   (Sun)

TAMRAZYAN, G.P.

Prospects for finding oil and gas in the Gousany field.
Neftegaz. geol. i geofiz. no.7:3-7 '63.

(MIRA 17:10)

1. Institut geologii im. I.M. Gubkina AN AzSSR.

OVNATANOV, S.T.; TAMRAZYAN, G.P.

Fossil mud volcano in the Peschanyy-More area. Neftegaz. geol.
i geofiz. no.11:33-34'63   (MIRA 17:7)

1. Neftepromyslovoye upravleniye "Ordzhonikidzeneft" i Institut
nefti AN AzSSR.

TAMRAZYAN, G.P.

Simultaneous spatial volcanic activity as an indication of
the presence of a deep fault and some problems of its
periodicity. Izv. vys. ucheb. zav.; geol. i razv. 6 no.2:
3-19 F '63.   (MIRA 16:6)

1. Institut geologii AN Azerbaydzhanskoy SSR im. I.M. Gubkina.
                        (Volcanoes)

OVNATANOV, S.T.; TAMRAZYAN, G.P.

Problem of reciprocal gradient variation with depth. Izv. vys. ucheb. zav.; neft' i gaz 6 no.10:15-18 '63.   (MIRA 17:3)

DURMISH'YAN, A.G.; TAMRAZYAN, G.P.

Transformation of the oil and gas pools of the Apsheron
Peninsula in connection with its geotectonic development.
Geol. nefti i gaza 8 no.3:41-46 Mr '64.   (MIRA 17:6)

1. Neftepromyslovoye upravleniye Karadagneft'.

SULIDI-KONDRAT'YEV, Ye.D. (Moskva); KOZLOV, V.V. (Moskva); TAMRAZYAN, G.P. (Baku);
FRANK-KAMENETSKIY, D.A., prof. (Moskva)

Articles on geological cycles. Priroda 53 no.1:102-111   '64.
(MIRA 17:2)

TAMRAZYAN, G.P., kand. geol.-mineral. nauk (Baku)

Ancient Volga near Baku. Priroda 53 no.10:102-104 '64. (MIRA 17:11)

TAMRAZYAN, G.P.

Structure and deep horizontal sections in the Apsheron Peninsula.
Dokl. AN SSSR 155 no.6:1337-1340 Ap '64.   (MIRA 17:4)

1. Predstavleno akademikom D.V.Nalivkinym.

TEMRAZYAN, G.P.

Principal differences in thermal conditions of the earth's interior in the European part and adjacent areas of the Asiatic part of the U.S.S.R. Dokl. AN SSSR 157 no. 2:337-340 Jl '64.
(MIRA 17:7)

1. Predstavleno akademikom D.V.Nalivkinym.

ACC NR: AR6022466   SOURCE CODE: UR/0169/66/000/003/G014/G014

AUTHOR: Tamrazyan, G. P.

TITLE: Certain aspects of the liberation of seismic energy from the earth's interior in connection with changes in tidal and other forces

SOURCE: Ref. zh. Geofiz, Abs. 3G96

REF SOURCE: Sb. v. Soveshchaniye po probl. planetol. 1965, L., 1965, 78-83

TOPIC TAGS: earthquake, seismic modeling, ocean tide

TRANSLATION: The author reaches the conclusion that the frequency of earthquakes may vary by as much as several hundred percent, depending on tidal forces. The relationship between this frequency and Moon phases is best defined for loci depths of 400 km. The relationship between earthquake frequency and cosmic conditions is discussed. In the author's opinion, faults possessing meridianal or nearly meridianal strikes are most readily affected by cosmic factors. Observations made on the Apsheron peninsula during 1957-1960 showed that a relationship between the tide inducing forces and seismicity occurs for earthquakes of force 10-13 but not for any weaker. A relationship apparently also exists between the 24-hour distribution of earthquakes on the Apsheron peninsula and cosmic conditions, geological structure and the stage of tectonic development. Occurrence of feeble earthquakes, $k = 4$ to 9, is well marked in afternoons.

UDC: 550.341.2

Card 1/2

ACC NR: AR6022466

This circumstance should be attributed to solar activity since only one maximum is attained every 24 hours. Had these earthquakes been due to tidal forces, there should have occurred two maxima every 24 hours. O. Kedrov.

SUB CODE: 08

Card- 2/2

USSR/General Biology. Genetics   B

Abs Jour : Ref Zhur-Biol., No 13, 1958, 57200

Author   : Tamrazyan L. Ye.
Inst   : Yerevan University
Title   : Effect of Different Methods of Pollination on
            the Heredity and Vitality of Sugar Beet.

Orig Pub : Nauchn. tr. Yerevansk. un-ta, 1956, ch, 2,
            95-104

Abstract : The author carried out the pollination of sugar
            beet with pollens of edible and feed sugar beet
            and came to the condlusion that different vari-
            eties react differently to pollination with fo-
            reign pollens, and to their own pollens in the
            presence of foreign pollens; that artificial
            pollination takes place better without castra-
            tion than with castration. Different methods of

Card 1/2

USSR/General Biology. Genetics   B

Abs Jour : Ref Zhur-Biol., No 13, 1958, 57200

Abstract : pollination cause a considerable change in
            the percent composition of dry matter in the
            juice; this indicates the possibility of in-
            creasing the sugar content in sugar beet by
            means of selection of corresponding compo-
            nents.

Card 2/2

38

LYSYKH, T.S., kand.tekhn.nauk; PASHIN, M.A., red.; LIPGART, A.A., red.; AL'-
PEROVICH, A.G., red.; BORISOV, S.G., red.; BRISKIN, M.I., red.;
DYBOV, O.V., red.; ZIL'BERBERG, Ya.G., red.; LOZAR', A.S.,red.;
LUNEV, I.S., red.; NAGAYEV, P.V., red.; PEVZNER, N.M., red.;
PRYADILOV, V.I., red.; RAMAYYA, K.S., red.; SAMOL', G.I., red.;
SEDOVA, Ye.V., red.; TAMBACHI, O.V., red.; KHANIN, N.S., red.;
CHAPCHAYEV, A.A., red.; CHISTOZVONOV, S.B., red.; SHKOL'NIKOV, E.M.,
red.; LEZHNEVA, G.V., red.izd-va; SMIRNOVA, G.V., tekhn.red.

[Design and investigation of performance of power disk brakes]
Issledovanie raboty diskovykh tormozov s usileniem i metod ikh
rascheta. Moskva, Gos.nauchno-issledovatel'skii avtomobil'noi i
avtomotornyi institut. Trudy, no.86)   (MIRA 12:8)

1. Gosudarstvennyy soyuznyy ordena Trudovogo Krasnogo Znameni
nauchno-issledovatel'skiy avtomobil'nyy i avtomotornyy institut.
                (Automobiles--Brakes)

TAMRUCHI, O., inzh.; FILIPPOV, A.

Let us talk about garages, comrades - automobile fans. Za rul. no.10:
7-8 O '57.   (MIRA 10:11)

1. Glavnyy inzhener "Giproavtotransa."
                                    (Garages)

PETRUSHOV, V.A., inzh.; PASHIN, M.A., red.; LIPGART, A.A., otv.red.;
    AL'PEROVICH, A.G., red.; BORISOV, S.G., red.; BRISKIN, M.I., red.;
    DYBOV, O.V., red.; ZIL'BERBERG, Ya.G., red.; LOZAR', A.S., red;
    LUNEV, I.S., red.; NAGAYEV, P.V., red.; PEVZNER, Ya.M., red.;
    PRYADILOV, V.I., red.; RAMAYYA, K.S., red.; SAMOL', G.I., red.;
    SEDOVA, Ye.V., red.; TAMRUCHI, O.V., red.; KHANIN, N.S., red.;
    CHAPCHAYEV, A.A., red.; CHISTOZVONOV, S.B., red.; SHKOL'NIKOV,
    E.M., red.; YEGORKINA, L.I., red.izd-va; GORDEYEVA, L.P., tekhn.
    red.

[Operational analysis of the multiplate friction transformer]
Analiz raboty mnogodiskovykh friktsionnykh transformatorov.
Moskva, Gos.nauchno-tekhn.izd-vo mashinostroitel'noi lit-ry,
1960. 79 p.(Moscow. Gosudarstvennyi nauchno-issledovatel'skii
avtomobil'nyi i avtomotornyi institut [Trudy], no.90).
                                                    (MIRA 13:8)
            (Motor vehicles--Transmission devices)

KISELEV, B.A., inzh.; LIPGART, A.A., otv.red.; PASHIN, M.A., red.; BORISOV,
        S.G., red.; BRISKIN, M.I., red.; BRYZGOV, N.N., red.; DYBOV, O.V.,
        red.; ZIL'BERBERG, Ya.G., red.; LOZAR', A.S., red.; LUNEV, I.S.,
        red.; NAGAYEV, P.V., red.; PEVZNER, Ya.M., red.; PRYADILOV, V.I.,
        red.; RAMAYYA, K.S., red.; SAMOL', G.I., red.; SEDOVA, Ye.V., red.;
        TAMRUCHI, O.V., red.; CHAPKEVICH, V.A., red.; CHISTOZVONOV, S.B.,
        red.; SHKOL'NIKOV, E.M., red.; SMIRNOVA, G.V., tekhn.red.

        [Investigation of the operation and gas-exchange of a loop-scavenged
        two-cycle motor-vehicle diesel engine] Issledovanie rabochego
        protsessa i gazoobmena dyukhtaktnogo avtomobilnogo dizelia s
        petlevoi produvkoi. Moskva, Mashgiz, 1961, 493 p. (Moskow.
        Gosudarstvennyi nauchno-issledovatel'skii avtomobil'nyi i
        avtomotornyi institut. Trudy, no.30).   (MIRA 16:8)
                            (Motor vehicles—Engines)

L 14455-66

ACC NR: AP6002960   (A)   SOURCE CODE: UR/0286/65/000/024/0128/0129

INVENTOR: Tamruchi, O. V.

ORG: none

TITLE: A ball-and-socket joint. Class 47, No. 177239

SOURCE: Byulleten' izobreteniy i tovarnykh znakov, no. 24, 1965, 128-129

TOPIC TAGS: mechanical engineering, mechanical fastener, structural hardware

ABSTRACT: This Author's Certificate introduces a ball-and-socket joint which con-
tains a frame, upper and lower inserts, an axle with the ball unit and a protective
case. The reliability, durability and damping properties of the joint are improved
by an elastic damping gasket fastened rigidly to the outer surface of each insert.
A supply groove is cut all the way through the lower insert and its gasket, and this
gasket is supported by an elastic damper rigidly fastened to the frame. The elastic
protective casing has an internal guard ring which is supported by the ball housing
and keeps the casing pressed against the journal.

UDC: 62-231.241

Card 1/2

L 14455-66

ACC NR: AP6002960

1 - inserts; 2 - supply groove; 3 - damper; 4 - protective elastic casing.

SUB CODE: 13/   SUBM DATE: 19Nov64

Card 2/2

L 06103-67 EWT(1) GW

ACC NR: AP6019515   (N)   SOURCE CODE: UR/0362/66/002/002/0174/0182

AUTHOR: Kagan, B. A.; Nekrasov, A. V.; Tamsalu, R. E.

ORG: Leningrad Hydrometeorological Institute (Leningradskiy gidrometeorologicheskiy institut)

TITLE: The influence of horizontal turbulent friction on tidal fluctuation at sea level

SOURCE: AN SSSR. Izvestiya. Fizika atmosfery i okeana, v. 2, no. 2, 1966, 174-182

TOPIC TAGS: hydrometeorology, turbulent flow, ocean current, ocean dynamics, ocean tide

ABSTRACT: A study is made of the influence of horizontal turbulent exchange on tidal fluctuations in the level of the Yellow Sea. It is established that a consideration of the horizontal turbulent exchange can be used to introduce a considerable degree of correction into calculated tide levels. Consideration of horizontal turbulent flow will not, however, lead to a basic change in tidal phenomena calculated for the Yellow Sea. Analysis of the results shows that the amphidromic points of the waves are displaced toward the center of the basin when horizontal turbulent exchange is considered. This causes the amplitudes of tide in the central portions of the basin to decrease, while tidal amplitudes at the northern and southern ends increase.

Card   1/2   UDC: 551.466.7

L 06103-67

ACC NR: AP6019515

Horizontal turbulent exchange causes a smoothing of transverse curvature. The influence of horizontal turbulent exchange leads to a reduction in the effect of depth variability. Orig. art. has: 5 formulas, 6 figures, and 1 table.

SUB CODE: 08/ SUBM DATE: 11May65/ ORIG REF: 005/ OTH REF: 007

Card 2/2 ℒC

PROCESSES AND PROPERTIES INDEX

Investigations on the possibility of improving the consistency of winter butter. W. Adriani and A. F. Tamsma.

Verslag. Landbouwk. Onderzoek 1946, No. 52(1)G, 1-23; *Chimie & industrie* 58, 372(1947).—In winter, butter has a tendency to become hard and brittle at ordinary temp. This defect can be overcome by taking certain precautions during manuf. (1) The texture which renders butter brittle should be destroyed. (2) The percentage of cryst. fats present in the butter at a given temp. (e.g., 13°) should be reduced as far as possible. To destroy the texture the butter should be worked at low temp.; if it is washed 3 times, the water should be at 9° or even a little lower; if very cold water were used the butter would lose its plasticity and the operation would require too much time. To reduce the percentage of cryst. fats as much as possible the cream should be cooled in the fermentation tanks in successive stages. After lab. tests the following procedure was adopted: After pasteurization the cream is cooled and introduced into the fermentation tanks at 14°. When the tank is filled (after about 8 hrs.) the temp. is raised to 22° and held for 1 hr. The cream is then cooled to 14° and held at this temp. overnight so that fermentation takes place chiefly at 14°. The ripened cream is churned at 14°, washed 3 times with water at 9° or lower, and finally worked. A. Papineau-Couture.

C-1

12

METALLURGICAL LITERATURE CLASSIFICATION

USSR/Soil Science. Organic Fertilizers.

Abs Jour: Ref Zhur-Biol., No 6, 1958, 24770.

Author : Zalys, A.; Tamulaityte, E.; Babraitis, V.
Inst   :
Title   : Utilization of Peat Fertilizers and Their Preparation
          in the Summer.

Orig Pub: Soc. zemes ukis, 1956, No 6, 5-12.

Abstract: No abstract.

Card   : 1/1

32

TAMULENIS, A.P.

Nomograms for determining the correction factors when bringing
industrial gas to standard conditions. Gaz. prom. 9 no.10:32-33
'64.
(MIRA 17:12)

TAMULEVICIUTE, D.

Remote results of the treatment of peptic ulcer with intravenous
infusions of novocaine. Sveik. apsaug. 9 no.2:10-16   F'64.

1. Respublikine Vilniaus klinine ligonine. Vyr.gyd.: V.Zygas.

*

TAMULEVICIUTE, D.

A case of malignant adenoma of the left adrenal cortex. Sveik. apsaug.
7 no.8:47-48 '62.

1. Resp. Vilniaus klinine ligonine.
                    (ADENOMA)   (ADRENAL CORTEX NEOPLASMS)

TAMURIDI, R.I.

[Exercise therapy for young children] Likuval'na fizychna kul'tura ditei rann'oho viku. Kyiv, Derzh. med. vid-vo URSR, 1955. 176 p.
(EXERCISE THERAPY)   (MLRA 10:2)

TAMURIDI, R. I., LYSAK, P. I.

Influence of the industrial work of students on their attitude
toward learning. Nauk. zap. Nauk.-dosl. inst. psykhol. 11:180-183
'59.   (MIRA 13:11)

(Industry and education)

TAMURIDI, R.I., kand.biol.nauk

Our faithful helpers. Nauka i zhyttia 9 no.10:36-38 O
'59.   (MIRA 13:2)
(LEFT-AND-RIGHT-HANDEDNESS)

TAMURIDI, R.I.

Functional asymmetry of the hands in the handling of objects by
infants. Pediatriia 37 no.9:90 S '59.   (MIRA 13:2)

1. Iz Instituta psikhologii Ministerstva prosveshcheniya USSR.
                    (LEFT AND RIGHT HANDEDNESS)

TAMUROV, N.G.; GVAY, P.I., dots., otvetstvennyy za vypusk

[Some problems in the bending of rectangular three-layer ortho-tropic plates with a filler] Nekotorye zadachi izgiba priamougol'-nykh trekhsloinykh ortotropnykh plastin s zapolnitelem. Dnepro-petrovsk, 1959, 17 p. (Dnepropetrovsk, Inzhenerno-stroitel'nyi institut. Nauchnoe soobshchenie, no.50).   (MIRA 14:4)

1. Zamestitel' direktora po nauchnoy chasti Dnepropetrovskogo inzhenerno-stroitel'nogo instituta (for Gvay).
                (Elastic plates and shells)

S/124/62/000/003/047/052
D237/D302

AUTHOR: Tamurov, N.G.

TITLE: Some problems of flexure of rectangular, three-layer, orthotropic filled plates

PERIODICAL: Referativnyy zhurnal, Mekhanika, no. 3, 1962, 16, abstract 3V92(Nauchn. soolshch. Dnepropetr. inzh.-stroit. in-t, 1959, no. 50, 18 pages)

TEXT: The equations of flexure of a three-layer plate composed of orthogonally anisotropic layers are derived under the following assumptions: 1) Supporting layers being thin and of high rigidity, are assumed to obey Kirchhof's hypothesis for plates; 2) The filler element, rectilinear and normal to the plate does not bend or elongate after the deformation, but remains straight, although it is no longer normal to the middle surface. The problems on flexure of the rectangular, freely supported plate under a uniform load, and under concentrated force and momentum are solved in terms of double trigonometric series. The solution of the problem of the bending of a rectangular plate freely supported by two opposite edges is sought

Card 1/2

Some problems of flexure of ...

S/124/62/000/003/047/052
D237/D302

in terms of ordinary trigonometric series. The author states that the solution for the semi-infinite plate freely supported by two edges under the sinusoidal load, is in good agreement with the exact solution of E.L. Bryukker [Translit.]. 5 references. [Abstractor's note: Complete translation].

Card 2/2

S/124/61/000/008/038/042
A001/A101

24.4260   3007

AUTHOR: Tamurov, N. G.

TITLE: Transverse bending of continuous three-layer plates with a rigid filler

PERIODICAL: Referativnyy zhurnal. Mekhanika, no. 8, 1961, 11, abstract 8V78 ("Sb. nauchn. tr. Dnepropetr. inzh.-stroit. in-t", 1960, no. 6, 44-54)

TEXT: The author investigates bending of a rectangular continuous plate supported on two long boundaries and fixed in arbitrary way on its short boundaries, subjected to a massive load uniformly distributed within each span. Displacements are found for a singled-out span subjected to: 1) uniformly distributed load; 2) static moments, applied in such a way that longitudinal forces of the external layers on the boundaries are equal to zero; 3) static moments applied in such a way that normal stresses do not change over the height of the external layers. The sum of the indicated solutions is the solution of the set up problem. To determine six unknown coefficients entering the solution, six equations are obtained from the condition of conjugation of the layers over the support. An example of determining these coefficients is given.
[Abstracter's note: Complete translation]   Yu. Kiryukhin
Card 1/1

28386

S/124/61/000/008/037/042
A001/A101

24.4200   3007

AUTHOR: Tamurov, N. G.

TITLE: Bending over a cylindrical surface of a continuous three-layer
             orthotropic plate with a filler

PERIODICAL: Referativnyy zhurnal. Mekhanika, no. 8, 1961, 11, abstract 8V77
             ("Sb. nauchn. tr. Dnepropetr. inzh.-stroit. in-t", 1960, no. 6,
             55-64)

TEXT: The author considers bending of a continuous infinitely-wide plate
subjected to a massive load uniformly distributed within each span; the work of
the filler for normal stresses in the plate plane is taken into account, as well
as non-uniformity of normal stress distribution over the height of external
layers. The problem is reduced to a system of equations of three moments and
three longitudinal forces. As a special case (shear strains are absent in the
filler) the known equation of three moments is obtained from these equations.
Formulae are given for determining stresses in the layers of the plate. The
results of solutions with and without taking into account filler's shear are

Card 1/2

Bending over a cylindrical surface ...

28386   S/124/61/000/008/037/042
A001/A101

compared. It is shown that if the work of filler crosscutting forces is not taken in consideration, large errors may result.

Yu. Kiryukhin

[Abstracter's note: Complete translation]

Card 2/2

TAMUROV, N.G.

Computation of nonstationary temperature fields in a two-layer
plate. Inzh.-fiz.zhur. 5 no.12:108-112 D '62.   (MIRA 16:2)

1. Inzhenerno-stroitel'nyy institut, Dnepropetrovsk.
                    (Heat—Conduction).

TAMUROV, N.G.

Equations of unsteady temperature fields in sandwich plates
with an unsymmetric structure. Inzh.-fiz.zhur. 6 no.10:72-75
O '63.   (MIRA 16:11)

1. Inzhenerno-stroitel'nyy institut, Dnepropetrovsk.

L 14730-65   BSD/AEDC(a)/SSD/ASD(f)-2/ASD(p)-3/AS(mp)-2

ACCESSION NR: AP5000113   8/0198/64/010/006/0664/0667

AUTHORS: Tamurov, N. G. (Tamurov, N. G.)(Dnipropetrovs'k)   B

TITLE: Unsteady-state heat conduction in triple-layered plates with second order boundary conditions

SOURCE: Prykladna mekhanika, v. 10, no. 6, 1964, 664-667

TOPIC TAGS: heat transfer, heat conduction, Laplace transformation, Fourier equation

ABSTRACT: Using the Laplace transformation method, the unsteady-state conduction temperature field within asymmetric triple-layer plates is calculated. The boundary conditions on the free surfaces assume various forms of heat flow. The results are reduced to the simpler case of symmetric triple-layer plates and the case of double-layered plates. Orig. art. has: 8 equations.

ASSOCIATION: Dnipropetrovs'kyy inzhenerno-budivel'nyy instytut (Dnepropetrovsk Engineering-Construction Institute)

SUBMITTED: 11Feb63   ENCL: 00

SUB CODE: AS, TD   NO REF SOV: 002   OTHER: 000

Card 1/1

TAMUROV, N.G. [Tamurov, M.H.] (Dnepropetrovsk)

Nonstationary heat conductivity in sandwich plates under boundary conditions of the second kind. Prykl. mekh. 10 no.6:664-667 '64.
(MIRA 18:2)

1. Dnepropetrovskiy inzhenerno-stroitel'nyy institut.

L 24052-66   EWT(d)/EWT(m)/EWP(v)/EWP(j)/EWP(k)/EWP(h)/EWP(l)   IJP(c)   RM

ACC NR: AP6011255   (A)   SOURCE CODE: UR/0413/66/000/006/0096/0096

39
B

INVENTOR: Tamruchi, O. V.; Remizov, G. K.; Istomin, N. P.

ORG: none

TITLE: Machine for the mechanical testing of rubber samples and similar elastic materials. Class 42, No. 179983

SOURCE: Izobreteniya, promyshlennyye obraztsy, tovarnyye znaki, no. 6, 1966, 96

TOPIC TAGS: rubber, elastic deformation, cyclic test, tensile test, test stand, test method laboratory instrument

ABSTRACT: An Author Certificate has been issued for a machine for the mechanical testing of rubber samples and similar elastics. The machine consists of two superposed parallel surfaces with an attachment for holding the sample. The lower surface elongates and compresses the sample through vertical reciprocating motion. To subject the sample to other types of simultaneous alternating deformation, the upper surface is capable of reciprocating horizontal motion. To provide twisting in compression and tension, the upper surface is capable of

Card 1/2   UDC: 678.01:539.3:620.172.05:620.173.05

L 24052-66

ACC NR: AP6011255

Fig. 1. Elastic-materials testing machine

reciprocating rotation. To provide alternating sheer, in compression and tension, the upper surface is capable of reciprocating straight-line motion in the horizontal plane. Orig. art. has: 1 figure.   [LB]

SUB CODE: 13, 14/ SUBM DATE: 27Nov6l

Card 2/2 dda

TAMUTIS, A. P.

TAMUTIS, A. P. - "An analysis of the generally used simplified methods of
equilibrating polygonometry and certain suggestions for improving them".
Minsk, 1955. Min Higher Education USSR. Belorussian Polytěchnic Inst imeni
I. V. Stalin, Chair of Geodesy. (Dissertation for the Degree of Candidate
of Technical Sciences).

SO: Knizhnaya Letopis' No. 46, 12 November 1955, Moscow

TAMUTIS, Z.P., kandidat tekhnicheskikh nauk.

Analyzing the accuracy of results of a separate balancing of a prolonged traverse survey. Geod.i kart. no.7:27-31 S '56.
(MLRA 9:11)

(Traverses (Surveying))

3(4)

AUTHOR: Tamutis, Z. P., Candidate of Technical Sciences

SOV/154-58-6-4/22

TITLE: Evaluation of Accuracy in Separate Adjusting of Unclosed Polygonal Traverses (Otsenka tochnosti pri razdel'nom uravnoveshivanii vytyanutogo poligonometricheskogo khoda)

PERIODICAL: Izvestiya vysshikh uchebnykh zavedeniy. Geodeziya i aerofotos"yemka, 1958, Nr 6, pp 19-26 (USSR)

ABSTRACT: This investigation concerns the evaluation of accuracy of co-ordinates of vertices of angles in separately adjusting an unclosed traverse with approximately equal sides. A comparison is made of the accuracy of coordinates in exact and separate adjustment. It is shown that the coordinates of the traverse center are obtained with equal squares of mean deviation both in exact and in separate adjustment. The formulae obtained (15) under consideration of (4) and (13) are identical with the analogous formulae of the book (Ref 1) which proves the correct-ness of the derivation given here. It is shown that the mean square longitudinal displacements of the points are equal both in the exact and in the separate adjustment. The trans-versal displacements, however, remain different. A diagram is

Card 1/2

SOV/154-58-6-4/22

Evaluation of Accuracy in Separate Adjusting of Unclosed Polygonal Traverses

given to illustrate these explanations. There are 2 figures, 1 table, and 4 references, 3 of which are Soviet.

ASSOCIATION: Kaunasskiy politekhnicheskiy institut (Kaunas Polytechnic Institute)

SUBMITTED: February 10, 1958

Card 2/2

3(4)
AUTHOR:

Tamutis, Z. P., Candidate of Technical Sciences

SOV/6-58-10-6/17

TITLE:

About the Adjustment of an Extended Polygonal Course (Ob uravnoveshivanii vytyanutogo poligonometricheskogo khoda)

PERIODICAL:

Geodeziya i kartografiya, 1958, Nr 10, pp 35-39, (USSR)

ABSTRACT:

It is more practical to apply complete formulae in the adjustment of polygonal courses and to find at once the corrections to the functions of the measured quantities, that means to the increase of the coordinates or to the coordinates. The derivation and application of such formulae for the adjustment of an extended polygonal course with approximately equal sides is given in this paper. The difference of the lengths of sides of the course may be partly considered in the calculation of the adjusted values of increase of the coordinates according to the formulae (4). Finally the formulae (12) for the final coordinates are derived with the number k . The exactness of the formulae (4) and (12) depends on the difference of the length of sides of the extended course. These formulae are exact when the sides have the same length. It is

Card 1/2

About the Adjustment of an Extended Polygonal Course   SOV/6-58-10-6/17

practical to apply these relatively simple formulae in the
adjustment of an extended polygonal course with about the
same lengths of sides. The tables 1 and 2 which are given
here and which have been made up for the application of these
formulae, make the calculations by far easier. The formulae
(4) and (12) are practically equivalent, both as to their
exactness as to the work expended on the calculation.
There are 2 tables and 2 references,   which are Soviet.

Card 2/2

S/035/61/000/006/044/044
A001/A101

3,4000

AUTHOR: Tamutis, Z.

TITLE: On rigorous balancing of polygonometric links

PERIODICAL: Referativnyy zhurnal. Astronomiya i Geodeziya, no. 6, 1961, 36, ab-
              stract 6G289 ("Tr. Kaunassk. politekhn. in-ta", 1960, v. 14, no. 2,
              47-50, Lithuanian, Russian summary)

TEXT: In practice of balancing polygonometric networks one employs, in
some cases, the rigorous balancing of individual links by the least-square method
after a non-rigorous adjustment of the network. On a great number of examples (40
links), the author shows that this method does not improve the results in compari-
son with the conventional distribution of closures in coordinate increments pro-
portional to lengths of the lines.

From author's summary

/B

[Abstracter's note: Complete translation]

Card 1/1

TAMUTIS, Z.F.

Adjustment of bound leveling networks by the polygon method.
Geod. i kart. no.10:16-20 O '61.   (MIRA 14:11)
              (Leveling)

AM4017079   BOOK EXPLOITATION   S/

Tamutis, Zigmantas Pranasovich

Adjustment of leveling and polygonometry; a practical manual
    (Uravnoveshivaniye nivelirovaniya i poligonometrii; praktiche-
    skoye rukovodstvo) Moscow, Gosgeoltekhizdat, 63.   0142 p.
    illus., biblio.   2000 copies printed.

TOPIC TAGS: surveying, geodesy, leveling, polygonometry, traverse,
adjustment of leveling, adjustment of polygonometry, surveying
accuracy

PURPOSE AND COVERAGE: This is a practical handbook for the adjust-
ment of results of measurements in leveling and polygonometry and
for estimates of the accuracy of measured and adjusted quantities
obtained both in local and official state surveying. Principal at-
tention is paid to leveling and polygonometric networks of lower
classes and orders. The textbook is intended for workers in geodesy

Card   1/3

AM4017079

and employs both rigorous and approximate methods. The author is
grateful to the staff members of the Department of Geodesy of
Kaunasskiy politekhnicheskiy institut (Kaunas Polytechnic Institute),
the reviewers docent Candidate of Technical Sciences A. N. Vy'sot-
skiy, docent Candidate of Technical Sciences V. P. Kozlov, and also
to docent M. Ratautas for useful advice in reviewing the manuscript.
The author is grateful to the editor, Doctor of Technical Sciences
P. A. Gaydayev, for thorough editing of the book.

TABLE OF CONTENTS [abridged]:

Card 2/3

AM4017079

surveys - - 54
Ch. III. Adjustment and estimate of accuracy of polygonometric
grids - - 82
Appendices - - 138
Literature - - 140

SUB CODE: AS   SUBMITTED: 29Apr63   NR REF SOV: 029

OTHER: 000   DATE ACQ: 28Oct63

Card 3/3

TAMUZ, V.P., inz. CSc. (Riga, U.S.S.R.)

Remarks on the J.Henrych article "Plastic construction deformations caused by impact load." Stav cas 13 no.4:250-251 '65.

40110

S/040/62/026/004/006/013
D/409/D301

11.2313

AUTHOR: Tamuzh, V.P. (Moscow)

TITLE: On a minimum principle in the dynamics of a rigid-plastic body

PERIODICAL: Prikladnaya matematika i mekhanika, v. 26, no. 4, 1962
            715 - 722

TEXT: It is shown that the actual strain-rate velocity minimize, at each moment of time, a certain functional. This minimum principle can be used for the approximate solution of dynamics problems of rigid-plastic bodies. The velocity-rate field is obtained by differentiation of the strain-rate field:

$$\dot{w}_i(x, y, z, t_0) = \left(\frac{\partial v_i(x, y, z, t)}{\partial t}\right)_{t=t_0}, \quad \ddot{\varepsilon}_{ij} = \frac{1}{2}(w_{i,j} + w_{j,i}). \quad (1.1)$$

Theorem. Among all the kinematically possible $\ddot{\varepsilon}_{ij}$, w_i and σ_{ij}, the actual $\ddot{\varepsilon}^*_{ij}$, w^*_i and o^*_{ij} at each moment of time, are those which mi-

Card 1/3

nimize the expression.

$$J = \int_V \frac{m\dot{w}_i^2}{2}\,dV - \int_V p_i w_i\,dV - \int_{S_T} T_i w_i\,ds + \int_V \sigma_{ij}\ddot{e}_{ij}\,dV \qquad (2.1)$$

where V is the volume of the rigid-plastic body and σ the stresses. The theorem is proved. The minimum principle stated, can be exten- -ded to velocity-rate fields with first-order discontinuities on surfaces which divide the body into a finite number of regions, in- side which the velocity-rates are continuous. Such a generalization is necessary, as in actual problems the velocity-rates are discon- tinuous as a rule. The extension to discontinuous fields involves the addition of terms to the functional (2.1). In the case of bend- ing of plates, it is convenient to use generalized variables. In this case too, the minimum principle holds. Finally, the minimum principle is illustrated by an example, namely the well-known prob- lem, solved by H. Hopkins and W. Prager (Ref. 6: On the Dynamics of Plastic Circular Plates ZAMP, 1954, 5). A hinged circular plate is loaded by a constant, uniformly-distributed pressure p during the time $0 \leq t < t_1$, after which the load is removed (Tresca's yield Card 2/3

On a minimum principle in the ...   S/040/62/026/004/006/013
                                           D409/D301

condition). The functional J is set up and, after calculations, one obtains the residual strain. There are 3 figures. The most important English-language reference reads as follows: T.Y. Thomas. Plastic Flow and Fracture in Solids. Acad. Press., 1961.

ASSOCIATION: Kafedra teorii plastichnosti MGU (Plasticity-Theory
             Department of Moscow State University)

SUBMITTED: April 25, 1962

Card 3/3

TAMUZH, V.P. (Moskva)

Plastic deformations of a circular arch and ring under the
action of dynamic loading. Izv. AN SSSR Otd. tekh. nauk. Mekh.
i mashinostr. no.2:58-65 Mr-Ap '63.   (MIRA 16:6)

(Arches)

L 36279-66   EWP(j)/EWT(m)/T   IJP(c)   RM/WW

ACC NR: AP6016817   SOURCE CODE: UR/0371/65/000/006/0063/0072

AUTHORS: Tamuzh, V. P.--Tamuzs, V.; Teters, G. A.--Teters, G.

43
B

ORG: Institute of mechanics of polymers, AN LatvSSR (Institut mekhaniki polimerov AN LatvSSR)

TITLE: Flexure and stability of nonlinear-elastic orthotropic plates

SOURCE: AN LatSSR. Izvestiya, Seriya fizicheskikh i tekhnicheskikh nauk, no. 6, 1965, 63-72

TOPIC TAGS: elastic plate, flexure vibration, nonlinear elasticity, orthotropic shell, shear strength, aerodynamic stability, supersonic vibration

ABSTRACT: The authors consider plates made of a nonlinear-elastic orthotropic medium, describing their deformation properties in terms of elastic tensors of fourth and eighth ranks. It is assumed that the shear rigidity in two of the planes is sufficiently high, and that the geometrical dimensions of the plate are such that the hypothesis of undeformed normals can be used. An equation for the flexure of the plate is obtained by summing the elementary moments over the height of the section and by using the equilibrium equation for the differential element of the plate. The influence of the nonlinear terms of this equation on the behavior of the plate is estimated. The dynamic stability of the plate against a force applied for a short time is then analyzed. This is followed by an analysis of parametric resonance and anal-

Card 1/2

L 36279-66

ACC NR: AP6016817

ysis of the stability of the plate when placed in a supersonic stream of gas, Orig.
art. has: 2 figures and 38 formulas.

SUB CODE: 20/ SUBM DATE: 02Apr65/ ORIG REF: 003/

Card 2/2

KASK, K.A.; PETUKHOV, Ye.F.; TAMVELIUS, Kh.Ya. [Tamvelius, H.J.]

Possible use of shale bitumen for the insulation of gas mains.
Khim. i tekh. gor. slan. i prod. ikh perer. no.9:255-261 '60.
(MIRA 15:6)

(Pipelines) (Bitumen) (Protective coatings)

R/009/60/000/005/003/003
A124/A026

AUTHOR: Tana, Ludovic

TITLE: Experience of the "Unirea" Metallurgical Plant - Cluj. Cementation
            in Gas

PERIODICAL: Metalurgia şi Construcţia de Maşini, 1960, No. 5, pp. 446 - 452

TEXT: The article presents a few experiments conducted by the Uzinele Met-
alurgice "Unirea" (Metallurgical Plant) in Cluj on the use of methane gas as car-
burizing agent. First experiments conducted in a furnace (Fig. 1) at a tempera-
ture of 820 - 850°C and a cementation time of 2.5 h did not supply satisfactory
results. Since the axles to be carburized were suspended vertically in the fur-
nace, the upper sections of the axles had a lower hardness degree than the lower
sections. This deficiency was tried to be eliminated by insulating the lid of
the furnace without achieving the expected results. The next improvement was the
installation of a fan (Fig. 4), which had to guarantee a uniform circulation of
the decomposed gases. Two experiments conducted at a carburizing temperature of
780 - 800°C and 900°C, supplied better, but still not satisfactory results. The
upper sections of the axles had not the same hardness as the lower ones. To elim-

Card 1/3

R/009/60/000/005/003/003
A124/A026

Experience of the "Unirea" Metallurgical Plant - Cluj.   Cementation in Gas

inate this deficiency, a simple artifice was applied. The sections of the axles
on the upper side of the carburizing furnace were introduced towards the internal
side of the hardening furnace, and then first introduced into the cooling agent.
Thus, a more accentuated hardening was achieved of that portion of the axle which
had a lower content of carbon. The results of an experiment conducted at a car-
burizing temperature of 900°C, a methane gas pressure of 100 col H_2O, and a hard-
ening temperature of 800 - 830°C, proved the correctness of this artifice. But
the axles had a coarse metallographic structure. This deficiency was eliminated
by applying a new method as follows: carburizing at 880 - 900°C for 2 h, first
hardening at 870 - 940°C and cooling in water, second hardening at 750 - 780°C
and cooling in water, and finally tempering by heating in oil at 150 - 180°C.
The results of this last experiment were highly satisfactory (Table 8). The fur-
nace described (Fig. 4) can also be used for the cementation of other parts, i.
e., bushings, gears, disks, etc. The operation of gas cementation can be divid-
ed into four main phases: 1) Preparation of the parts for cementation; 2) ce-
mentation; 3) cooling of the cemented parts; and 4) hardening of the connected
parts. Brief reference is made to all phases and to the advantages of gas ce-

Card 2/3

R/009/60/000/005/003/003
A124/A026

Experience of the "Unirea" Metallurgical Plant - Cluj. Cementation in Gas

mentation as compared with cementation in solid media. There are 7 figures, 9
tables and 2 references: 1 Rumanian and 1 Hungarian.

Card 3/3

TANABAYEV, B.

Decrease in the velocity of a meteor's motion in relation to its brightness and color according to visual observations. Izv.AN Turk.SSR no.4:129-130 '57.   (MIRA 10:10)

1. Institut fiziki i geofiziki AN Turkmenskoy SSR.
(Meteors)

TANABAYEV, B.

     Studying the catalog of telescopic meteors. Izv.AN Turk. SSR
no.5:150-151 '57.   (MIRA 10:10)

     1.Institut fiziki i geofiziki AN Turkmenskoy SSR.
                  (Meteors)

TANABAYEV, B.

Distribution of the observable velocities of meteors according
to the data of the 19th century. Izv.AN Turk. SSR no.5:152 '57.

1.Institut fiziki i geofiziki AN Turkmenskoy SSR.
                    (Meteors)

9.4300 (32.03, 104 : ...)
9.7140
15.2210   1275 1145, 1136

86717

R/004/60/000/007/002/002
A231/A026

AUTHORS: Ivaşcu, Vasile, Engineer, Chief of Laboratory; Rozemberg, Mihai,
            Candidate of Sciences, University Lecturer; Tanach, Valentin,
            Engineer, Researcher; and, Cîrlan, Lucia, Engineer, Chief Research-
            er; (Bucharest)

TITLE: Magnetic Ferrite Cores for Application in Radioengineering, Auto-
            mation and Telecommunications. (Ferrites With Rectangular Hystere-
            sis Loops)

TEXT: The authors present the results of some studies conducted at the
ICET (Electric Engineering Research Institute) with regard to the production of
magnetic oxide materials (ferrites) with a rectangular hysteresis loop, to be
used in electronic computers, automatic telephone exchanges, etc. The ICET in-
vestigations led to the development of several types of memorizing and switch
cores with the corresponding characteristics presented in Table 1. Reference
is made to J. Goodenough (Ref. 3) who described the properties of ferrites with
a rectangular hysteresis loop. For their investigations, the authors prepared

Card 1/3

86717

R/004/60/000/007/002/002
A231/A026

Magnetic Ferrite Cores for Application in Radioengineering, Automation and Tele-communications. (Ferrites With Rectangular Hysteresis Loops)

the following three compositions: "HA", with ratio of $\frac{MnO}{MgO} = \frac{1}{2}$; and "H", with a ratio of $\frac{MnO}{MgO} = \frac{8}{3}$; and "V", a composition similar to in which 50 % of the

MgO have been replaced by ZnO. The granulation of the raw material was of the 1μ order. Toroidal-shape pieces of different sizes have been prepared (Table 2). Measurements of size, density, hysteresis loop, initial permeability, reversal time, and variations of the hysteresis loop with the temperature have been accomplished. The results of the measurements are compiled in Figures 6, 7, 8, and 9, and Tables 3 and 4. The "HA" composition proved to be useful for memorizing circuits. The "H" composition can be used in switching circuits and telecommunications due to a low R_g coefficient, although the "V" composition is more advantageous for these purposes because of the low coercive force ($<$ 0.2 Oe). Different factors of heat treatment, i.e., temperature, cooling time, etc., have a certain influence on the properties of these compositions. An increase of the temperature and of the duration of the heat treatment, generally increases

Card 2/3

86717

R/004/60/000/007/002/002
A231/A026

Magnetic Ferrite Cores for Application in Radioengineering, Automation and Tele-communications. (Ferrites With Rectangular Hysteresis Loops)

the B_m maximum induction and the B_r/B_s ratio, but reduces the coercive force. An exception could be found at the H (I) composition after slow cooling. The characteristics of the cores are also depending on their dimensions. The values of the initial permeability of the cores produced (Table 3) are a direct conse-quence of the property of composition and treatment. The μ_i value drops with the increase of the MnO content from the "H" composition to the "HA" composition via the "V" composition. With the "H" composition, μ increases with the grow-ing treatment temperature, or with the duration of the treatment. "HA", type IV, and "V", type II cores treated at 1,350° for 5 hours and then cooled rapid-ly, proved to be the best materials for memorizing and switch cores. In func-tion of their application for which the cores with a rectangular hysteresis loop are determined, the following parameters are decisive for obtaining good perfor-mances: composition, shape and size of the cores, and heat treatment conditions. There are 10 figures, 5 tables, and 7 references: 3 Soviet, 3 English, 1 French. ASSOCIATION: ICET (El. Engineering Research Institute),(Ivașcu, Tanach, Cîrlan);
          Universitatea "C.I. Parhon" (University) (Rozemberg)
SUBMITTED: February 25, 1960
Card 3/3

L 33043-66

ACC NR: AP6024230   SOURCE CODE: RU/0005/65/000/003/0080/0084

AUTHOR: Tanach, Valentin—Tanakh, V. (Engineer); Stanciulea, Lucia (Engineer);
David, Bella (Engineer); Cojocaru, Zoe (Engineer); Fridman, Alexandru (Physicist), 35

ORG: /Tanach; Cojocaru/ Electronic Works (Uz. Electronika); /Stanciulea; David;
Fridman/ ICPE

TITLE: Achievements in the field of perminvar-type ferrites and their applications

SOURCE: Telecomunicatii, no. 3, 1965, 80-84

TOPIC TAGS: ferrite, high frequency

ABSTRACT: The authors discuss the theory underlying the development of perminvar-
type ferrites with superior high-frequency performance and describe their work in this
field. Experimental results are presented for some of the materials prepared by the
authors, and their fields of application are discussed. Orig. art. has: 4 figures
and 3 tables. /Based on authors' Eng. abst./ /JPRS/

SUB CODE: 11, 09 / SUBM DATE: 20Feb64 / ORIG REF: 002 / OTH REF: 007

Card 1/1   UDC: 621.318.13

L 48237-65   EWT(l)/EEC-4/EEC(t)/T/FCS(k)   Pl-4/Pac-4/Pj-4/Pl-4   WR   48
                                                                              B

ACCESSION NR: AP5014065   RU/0005/64/008/005/0222/0226

AUTHOR: Tanach, Valentin (Engineer); Stanciulea, Lucia (Engineer); Fridman, Alexandru (Physicist)

TITLE: Magnetic antennas for short waves

SOURCE: Telecomunicatii, v. 8, no. 5, 1964, 222-226

TOPIC TAGS: antenna, antenna engineering, ferromagnetic material

ABSTRACT: (Author's English summary modified): After reviewing the characteristics of a new ferrite type with perminvar characteristics which led to the elaboration of materials with high permittivity and low short-wave losses, the authors report successful use of this type of ferrite in form of a rod as a replacement for the currently-used electric short-wave antenna. Orig. art. has 4 figures, 8 formulas and 2 tables.

ASSOCIATION: none

SUBMITTED: 00   ENCL: 00   SUB CODE: EC

NO REF SOV: 001   OTHER: 002   JPRS

Card 1/1

L 22605-65   EWT(1)/EEC(b)-2/EED-2/EWA(h)   Peb   IJP(c)

ACCESSION NR: AP5002362   P/0053/64/000/012/0639/0645

AUTHOR: Tanach, V.; Cojocaru, Z.; Stanciulea, L.; Fridman, A.; David, B.

TITLE: New developments in the field of perminvar ferrites and their applications

25

SOURCE: Przeglad elektroniki, no. 12, 1964, 639-645

TOPIC TAGS: ferrite, perminvar ferrite, temperature dependence, field dependence, permeability, quality factor

ABSTRACT: Tests were made of nickel-zinc ferrites with cobalt additive for the purpose of establishing the connection between the production technology and the properties of perminvar ferrites. The tested ferrites covered a wide range of compositions, and the best results were obtained with ferrites in which the oxide contained a large fraction (up to 50%) geothite. The ZnO/NiO ratio ranged from 0 to 2.45, and the Fe_2O_3 excess was maintained constant. The resultant ferrites had initial permeabilities up to 200 G/Oe and very low losses (Q up to 2000) up to 200 Mc. The initial permeability was greatly affected by the sintering temperature and by the external magnetic field. Several applications of such per-

Card 1/2

L 22605-65
ACCESSION NR: AP5002362   2

minvar ferrites are discussed; these include antenna wires and cores for radio
and television coils and filters at various frequencies. Some theoretical prob-
lems concerning the mechanism of production of the perminvar structure and the
influence of the temperature and of the external field remain to be solved, and
the question of the applicability of such ferrites for miniature and micro-
miniature circuits remains open. Orig. art. has 4 tables.

ASSOCIATION: Electronic Enterprises, Bucharest; Electronic Scientific-Research
Institute, Bucharest.

SUBMITTED: 15Jul64   ENCL: 00   SUB CODE: EM, MM

NR REF SOV: 000   OTHER: 009

Card 2/2

TANACH, Valentin, ing.; STANCIULEA, Lucia, ing.; DAVID, Bella, ing.; COJCCARU,
Zoe, ing.; FRIDMAN, Alexandru, fiz.

Achievements in the field of perminvar-type ferrites and their
applications. Telecomunicatii 9 no.3:80-84 Mr '65.

1. Research and Electrical Engineering Planning Institute,
Bucharest (for Stanciulea, David, Fridman).

TANACHEVA, M.I.

New data on the distribution of the Discorbis containing zone in the West Siberian Plain. Trudy SNIIGGIMS no.23:18-25 '62.

(MIRA 16:9)

(West Siberian Plain—Foraminifera, Fossil)

TARASOV, I.S.

Analytical method of calculating the unsteady flow of tail water
of a hydroelectric power station. Trudy Lengidroproekta no.1:114-
221 '64.   (MIRA 18:10)

FORRAI,Jeno,dr.; TANAI,Janos,dr.

Nearthrosis interspinosa,Baastrup's disease. Magy radiol 12 no.1: 23-26 Mr '60.

1.A Magyar Nephadsereg Igeszsegugyi Szolgalatanak kozlemenye.
(SPINE dis.)

PAL, Istvan, dr.; TANAI, Janos, dr.

Contributions to the problem of Tietze's syndrome. Orv.hetil.
101 no.34:1203-1205 21 Ag '60.

1. Magyar Nephadsereg Egeszsegugyi Szolgalata.
          (RIBS dis)

PAL, Istvan, dr.; TANAI, Janos, dr.

On the diagnostic value of lumbosacral striae. Orv. hetil. 102 no.43:
2033-2034 22 0 '61.

1. Magyar Nephadsereg Egeszsegugyi Szolgalata.

(LUMBOSACRAL REGION)

PEDIATRICS

HUNGARY

TANAI, Janos, Dr, FORRAI, Jeno, Dr, RENYI, Kazmer, Dr; [affiliations not given].

"The Role of Scheuermann's Disease in Backaches Among the Young."

Abstract: [Authors' Hungarian summary] Following a description of the clinical-radiological symptoms of Scheuermann's disease, the results of the examination of 119 young patients with backache are reported. With 27 typical cases (22.7 per cent) of the disease, an additional 34 (28.6 per cent) of the patients could be classified in the same group on the basis of the mild changes discovered. In a healthy control group, only 3.9 per cent had similar changes. On the basis of this pronounced statistical difference, the radiological changes described are looked upon as the cause of backache among the young patients. In the authors' opinion, the sometimes persistent backache of the young can often be elucidated only by the correct interpretation of the above changes which are not always pronounced. 3 Eastern European, 19 Western references.

1/1

PETHO, Erzsi; SZABO, Janos; BODRI, Andras; NAGY, Bela, mernok; TANAI, Sandor

Four from among many. Ujit lap 13 no.10:6 My '61.

1. Muvezeto, Ganz-MAVAG. (for Szabo) 2. Maros, Ganz-MAVAG.(for Bodri)
3. Ganz-MAVAG. 4. Lakatos, Ganz-MAVAG (for Tanai)

(Hungary—Machinery industry)
(Hungary—Iron industry and trade)
(Hungary—Steel industry and trade)

GAUKHMAN, R. (UA3CH); TANAKIN, I. (UA3IM)

Regenerative preselector-converter. Radio no.2:17-18 F '65.

(MIRA 18:7)

TANAN, P.

      Cuba is free. Voen. znan. 42 no.2:16-17 ? '66.

                                  (MIRA 19:1)

VERBOLOVICH, P.A.; PLESHKOVA, S.M.; TANANA, G.D.

Histochemical method for determining myoglobin (preliminary report). Zdrav. kazakh. 21 no.12:29-33 '61.   (MIRA 15:3)

1. Iz kafedry biologicheskoy khimii (zav. - doktor meditsinskikh nauk P.A. Verbolovich) Kazakhskogo meditsinskogo instituta i kafedry gistologii (zav. - prof. F.M. Mukhamedgaliyev) Alma-Atinskogo zooveterinarnogo instituta.
(MYOGLOBIN)

VERBOLOVICH, P.A.; TANANA, G.D.; PLESHKOVA, S.M.

Histochemical study of the localization of myoglobin in muscles. Zdrav. Kazakh. 22 no.9:47-51 '62.

(MIRA 17:2)

1. Iz kafedry biologicheskoy khimii (zav. - doktor med. nauk P.A. Verbolovich) Kazakhskogo meditsinskogo instituta.

TANANAKIN, Ye.I.; TANZYBAYEV, M.G., kand.sel'skokhozyaystvennykh nauk;
MOLDAVSKIY, D.D.

Introduce cultivation practices controlling erosion in Khakassia.
Zemledelie 25 no.2:44-48 F '63.
(MIRA 16:5)

1. Direktor Khakasskoy sel'skohozyaystvennoy opytnoy stantsii
(for Tananakin). 2. Glavnyy agronom Upravleniya zony Vostochnoy
Sibiri Ministerstva proizvodstva i zagotovok RSFSR (for Moldavskiy).
(Khakass Autonomous Province--Soil conservation)

PALATNIK, L.S.; TANANKO, I.A.

Characteristics of diffusion redistribution of carbon in undercooled austenite. Fiz. met. i metalloved. 9 no. 4:554-557 Ap '60.

(MIRA 14:5)

1. Khar'kovskiy politekhnicheskiy institut im. V.I. Lenina.
(Diffusion) (Steel—Metallography)